

∅150 AG series

x172x51mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Al die-casting & Plastic
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

Model	*Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGE15051_24J	B	24	14.0~26.4	1.50	3500	7.79	275.0	22.5	0.89	57.0	800
AGE15051_48J	B	48	28.0~56.0	0.90	3500	7.79	275.0	22.5	0.89	57.0	800
AGE15051_24L	B	24	14.0~26.4	2.10	4000	8.69	307.0	28.0	1.10	61.5	800
AGE15051_48L	B	48	28.0~56.0	1.20	4000	8.69	307.0	28.0	1.10	61.5	800
AGE15051_24M	B	24	14.0~26.4	2.88	4400	9.40	332.0	34.2	1.35	63.5	800
AGE15051_48M	B	48	28.0~56.0	1.50	4400	9.40	332.0	34.2	1.35	63.5	800

*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

