

## 80 cooling fan ×80×10mm



### General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dba
SP80B05L-10DL	B / S	5	3.6~6.8	0.21	1.05	2500	0.51	18.11	1.29	0.05	26.4
SP80B12L-10DL	B / S	12	7.0~13.2	0.15	1.80	2500	0.51	18.11	1.29	0.05	26.4
SP80B24L-10DL	B / S	24	14.0~26.4	0.08	1.92	2500	0.51	18.11	1.29	0.05	26.4
SP80B12M-10DL	B / S	12	7.0~13.2	0.19	2.28	3000	0.61	21.71	1.81	0.07	30.2
SP80B24M-10DL	B / S	24	14.0~26.4	0.13	3.12	3000	0.61	21.71	1.81	0.07	30.2
SP80B12H-10DL	B / S	12	7.0~13.2	0.25	3.00	3300	0.67	23.81	2.40	0.08	32.4
SP80B24H-10DL	B / S	24	14.0~26.4	0.16	3.84	3300	0.67	23.81	2.40	0.08	32.4

\*Bearing system B: Two Ball Bearing S: Sleeve Bearing

