

## 92 cooling fan

×92×38mm



### General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dba
SP92B12L-38DL	B / S	12	7.0~13.2	0.55	6.60	4400	2.66	94.11	14.58	0.57	51.2
SP92B24L-38DL	B / S	24	14.0~26.4	0.30	7.20	4400	2.66	94.11	14.58	0.57	51.2
SP92B48L-38DL	B / S	48	28.0~56.0	0.25	12.00	4400	2.66	94.11	14.58	0.57	51.2
SP92B12M-38DL	B / S	12	7.0~13.2	0.68	8.16	4800	2.90	102.55	17.33	0.68	54.1
SP92B24M-38DL	B / S	24	14.0~26.4	0.33	7.92	4800	2.90	102.55	17.33	0.68	54.1
SP92B48M-38DL	B / S	48	28.0~56.0	0.21	10.08	4800	2.90	102.55	17.33	0.68	54.1
SP92B12H-38DL	B / S	12	7.0~13.2	1.22	14.64	6000	3.63	128.13	25.94	1.02	60.5
SP92B24H-38DL	B / S	24	14.0~26.4	0.68	16.32	6000	3.63	128.13	25.94	1.02	60.5
SP92B48H-38DL	B / S	48	28.0~56.0	0.36	17.28	6000	3.63	128.13	25.94	1.02	60.5
SP92B12U-38DL	B / S	12	7.0~13.2	1.96	23.52	7000	4.31	152.32	36.84	1.45	64.4
SP92B24U-38DL	B / S	24	14.0~26.4	1.02	24.48	7000	4.31	152.32	36.84	1.45	64.4
SP92B48U-38DL	B / S	48	28.0~56.0	0.60	28.80	7000	4.31	152.32	36.84	1.45	64.4
SP92B12HU-38DL	B / S	12	7.0~13.2	3.10	37.20	8000	4.95	174.98	46.03	1.81	66.5
SP92B24HU-38DL	B / S	24	14.0~26.4	1.45	34.80	8000	4.95	174.98	46.03	1.81	66.5

\*Bearing system B: Two Ball Bearing S: Sleeve Bearing

