

40 DC Blower

×40×10mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音
型号	B/S	V	V	A	W	RPM	m ³ /min CFM	mm-H ₂ O In-H ₂ O	dba
SP40S05L-10DL	B/S	5	4.5~5.5	0.06	0.30	5500	0.055 1.94	5.37 0.21	28.0
SP40S12L-10DL	B/S	12	7.0~13.2	0.04	0.48	5500	0.055 1.94	5.37 0.21	28.0
SP40S05M-10DL	B/S	5	4.5~5.5	0.08	0.40	6500	0.065 2.30	7.93 0.31	29.5
SP40S12M-10DL	B/S	12	7.0~13.2	0.05	0.60	6500	0.065 2.30	7.93 0.31	29.5
SP40S05H-10DL	B/S	5	4.5~5.5	0.11	0.55	7500	0.074 2.61	10.85 0.43	32.5
SP40S12H-10DL	B/S	12	7.0~13.2	0.06	0.72	7500	0.074 2.61	10.85 0.43	32.5
SP40S05U-10DL	B/S	5	4.5~5.5	0.16	0.80	8500	0.085 3.00	14.33 0.56	34.5
SP40S12U-10DL	B/S	12	7.0~13.2	0.08	0.96	8500	0.085 3.00	14.33 0.56	34.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

